

DL01

Long Haul Drive

Extra deep tread, exceptional traction and high mileage are all built into the DL01. Designed to provide a new level of performance in all driving conditions, the DL01 features improved casing profile technology for higher durability and easy retreading.



Sizes & Specifications (Pattern Code: DL01)																
S-Code	Size	Ply Rating	Type	Measuring Rim	Max. Air (PSI)		Max. Load (LBS)		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile	Sidewall Type	SLR (Inch)	Speed Limit
					S	D	S	D								
3000828	11R22.5	14	T/L	8.25	105	105	6,175	5,840	42.1	11.2	8.2	30	496	SBL	19.6	75
3000957 *	11R22.5	16	T/L	8.25	120	120	6,610	6,005	42.1	11.2	8.2	30	496	SBL	19.7	75
3000829	11R24.5	14	T/L	8.25	105	105	6,610	6,005	44.1	11.0	8.2	30	471	SBL	20.6	75
3000958	11R24.5	16	T/L	8.25	120	120	7,160	6,610	44.1	11.0	8.2	30	471	SBL	20.6	75
3000598	295/75R22.5	14	T/L	8.25	110	110	6,175	5,675	41.0	11.6	8.6	30	507	SBL	19.2	75

* OE : Navistar • Use inflation pressure specifications on vehicle tire placard. • Tire construction and material specifications subject to change without notice or obligation.

Recommended Vehicle Types & Position



DL07

Long Haul Drive

Developed with an aggressive block pattern, the DL07 will provide superior traction for line-haul applications. The wider, deeper grooves with enhanced stone ejector platforms will prevent stone drilling and maximize removal mileage. Advanced tread design and carcass construction provides even wear patterns, equal weight/torque distribution, reduced heat buildup, and increased fuel efficiency.



Sizes & Specifications (Pattern Code: DL01)																
S-Code	Size	Ply Rating	Type	Measuring Rim	Max. Air (PSI)		Max. Load (LBS)		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile	Sidewall Type	SLR (Inch)	Speed Limit
					S	D	S	D								
3001587	285/75R24.5	14	T/L	8.25	110	110	6,175	5,675	42.2	11.3	9.3	31	492	SBL	19.8	75

Expanded sizes to follow. • Use inflation pressure specifications on vehicle tire placard. • Tire construction and material specifications subject to change without notice or obligation.

Recommended Vehicle Types & Position



Z59/Z59W

Drive Position / Traction

Developed for highway bus and truck. Deeper and wider tread block type on the drive position improves wear resistance, while variable pitches of tread reduce road noise.



Sizes & Specifications (Pattern Code: Z59)																
S-Code	Size	Ply Rating	Type	Measuring Rim	Max. Air (PSI)		Max. Load (LBS)		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile	Sidewall Type	SLR (Inch)	Speed Limit
					S	D	S	D								
T0000CK3000360	10.00R20	14	T/T	7.50	105	105	6,175	5,840	41.9	10.8	8.0	28	496	SBL	19.6	75
3000368	11R22.5	14	T/L	8.25	105	105	6,175	5,840	41.9	10.9	8.0	28	496	SBL	19.6	75
3000369	11R22.5	16	T/L	8.25	120	120	6,610	6,005	41.9	10.9	8.0	28	496	SBL	19.6	75
3000370	12R22.5	16	T/L	9.00	120	120	7,390	6,780	43.0	11.6	9.0	28	483	SBL	20.0	75
3000371	11R24.5	14	T/L	8.25	105	105	6,610	6,005	43.9	10.8	8.0	27	474	SBL	20.5	75
3000372	11R24.5	16	T/L	8.25	120	120	7,160	6,610	43.9	10.8	8.0	27	474	SBL	20.5	75

Sizes & Specifications (Pattern Code: Z59W)																
S-Code	Size	Ply Rating	Type	Measuring Rim	Max. Air (PSI)		Max. Load (LBS)		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile	Sidewall Type	SLR (Inch)	Speed Limit
					S	D	S	D								
3000374	295/75R22.5	14	T/L	8.25	110	110	6,175	5,675	40.9	11.3	7.8	27	509	SBL	19.1	75
3000376	285/75R24.5	14	T/L	8.25	110	110	6,175	5,675	42.0	11.0	7.8	27	495	SBL	19.6	75

• Technical data subject to change without prior notice.

Recommended Vehicle Types & Position



Reading a Hankook TBR tire

A H 1 2

POSITION APPLICATION SEQUENCE NUMBER

	Long Haul	Regional Haul	Urban	On & Off, Off	Mud & Snow
A All position	AL	AH	AU	AM	AW
D Drive	DL	DH	DU	DM	DW
T Trailer	TL	TH			