

Dimension Data



Dynapro MT



• Q-Rated

The Dynapro MT is designed for serious off-road enthusiasts. Special design features such as tapered “V” shaped tread blocks provide better grip in mud, sand and snow. Unique stone “ejector” grooves along with a rugged shoulder help prevent damage from impacts. It is this attention to design that has helped make the Dynapro MT the tire of choice for extreme off-roading.

15"-17" sizes are pinned for studs (TSMI No. 16 Recommended for Stud Pin)

S-Code	Size	Ply Rating	L / I & SS	Measuring Rim	Rim Width Range	Max. Load		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile
						psi	lbs					
•2000981*	LT215/75R15	6	100/97Q	6.0	5.5-7.0	S 50 D 50	1,765 1,610	27.9	8.4	6.8	16.5	745
•2000978*	LT235/75R15	6	104/101Q	6.5	6.0-7.0	S 50 D 50	1,985 1,820	29.1	9.1	7.2	17.5	714
2001220	LT305/70R16 (33X12.50R16)	8	118/115Q	9.0	8.0-9.5	S 50 D 50	2,910 2,680	33.1	12.2	9.4	19.5	628
2001285	LT225/75R16	10	115/112Q	6.0	6.0-7.0	S 80 D 80	2,680 2,470	29.4	8.9	6.9	18.5	705
2001283	LT245/75R16	10	120/116Q	7.0	6.5-8.0	S 80 D 80	3,042 2,778	30.7	9.9	7.7	18.5	676
2001027*	LT265/75R16	10	123/120Q	7.5	7.0-8.0	S 80 D 80	3,415 3,085	31.9	10.8	8.2	18.5	652
2001028*	LT285/75R16	10	126/123Q	8.0	7.5-9.0	S 80 D 80	3,750 3,415	33.0	11.6	8.7	18.5	629
2001219*	LT295/75R16 (33X11.50R16)	8	123/120Q	8.0	7.5-9.5	S 65 D 65	3,415 3,085	33.6	11.6	9.0	19.5	618
2001295*	LT315/75R16 (35X12.50R16)	10	127Q	8.5	8.0-10.0	S 65	3,860	34.8	12.3	9.4	19.5	597
2001286	LT215/85R16	10	115/112Q	6.0	5.5-7.0	S 80 D 80	2,680 2,470	30.6	8.8	6.8	18.5	678
2001287	LT235/85R16	10	120/116Q	6.5	6.0-7.5	S 80 D 80	3,042 2,778	32.0	9.5	7.2	18.5	650
2001129	LT265/70R17 (32X10.50R17)	10	121/118Q	8.0	7.0-8.5	S 80 D 80	3,195 2,910	31.9	10.7	8.3	18.5	651
2001222	LT285/70R17 (33X11.50R17)	8	121/118Q	8.5	7.5-9.0	S 65 D 65	3,195 2,910	33.0	11.5	8.9	19.5	629
2001223	LT315/70R17 (35X12.50R17)	8	121/118Q	9.5	8.5-10.0	S 50 D 50	3,195 2,910	34.6	12.7	9.7	19.5	600
2001560	LT255/75R17	10	121/118Q	7.0	6.5-8.5	S 80 D 80	3,195 2,910	32.1	10.0	7.8	18.5	647
2001227	LT325/60R18 (33X13.00R18)	10	124/121Q	9.5	9.0-12.0	S 65 D 65	3,525 3,195	33.6	13.0	10.1	19.5	618
2001300	LT275/65R18 (32X11.00R18)	10	123/120Q	8.0	7.5-9.0	S 80 D 80	3,415 3,085	32.3	11.0	8.7	20.0	643
2001226	LT325/65R18 (35X13.00R18)	10	127/124Q	9.5	9.0-12.0	S 65 D 65	3,860 3,525	34.8	13.0	10.1	19.5	597
2000976*	30X9.50R15LT	6	104Q	7.5	6.5-8.5	S 50	1,985	29.8	9.5	7.6	18.5	697
2000789*	31X10.50R15LT	6	109Q	8.5	7.0-9.0	S 50	2,270	30.7	10.6	8.4	18.5	677
2000980*	32X11.50R15LT	6	113Q	9.0	8.0-10.0	S 50	2,535	31.8	10.8	9.1	18.5	653
2000977*	33X12.50R15LT	6	108Q	10.0	8.5-11.0	S 50	2,225	32.8	12.2	9.8	18.5	633
2002016	35X12.50R15LT	6	113Q	10.0	8.5-11.0	S 35	2,535	34.8	12.9	9.8	19.5	597
2001297	35X12.50R17LT	10	121Q	10.0	8.5-11.0	S 65	3,195	34.8	12.9	9.8	20.0	597
2002005	37X12.50R17LT	8	124Q	10.0	8.5-11.0	S 65	3,525	36.8	12.9	9.8	21.0	565
2001298	35X12.50R18LT	10	123Q	10.0	8.5-11.0	S 65	3,415	34.8	12.9	9.8	20.0	597
2001275	37X12.50R18LT	8	123Q	10.0	8.5-11.0	S 50	3,415	36.8	12.9	9.8	21.0	564
2001277	35X12.50R20LT	10	121Q	10.0	8.5-11.0	S 65	3,195	34.8	12.9	9.8	20.0	597
2001276	37X13.50R20LT	10	127Q	11.0	8.5-11.0	S 50	3,860	36.8	13.6	10.9	21.0	564
2001281	38X15.50R20LT	8	125Q	12.0	11.0-13.0	S 50	3,640	37.8	15.4	12.3	21.0	550
2001278	37X13.50R22LT	10	123Q	11.0	8.5-11.0	S 50	3,420	36.8	13.6	10.9	21.0	564

* WSW : White Sidewall
 •TSMI No.13 Recommended for Stud Pin.
 TSMI No.16 Recommended for Stud Pin.
 Technical data subject to change without prior notice.