

Dimension Data



Silica COMPOUND



M+S

i*Pike RW11



- Q & T-Rated
- 50/55/60/65/70/75/80/85 Series

The i*Pike RW11 is a Premium Studdable winter tire designed for SUVs and Light Trucks.



Meets the severe snow service requirement of the Rubber Manufacturer's Association (RMA)

S-Code	Size	L / I & SS	Measuring Rim	Rim Width Range	Max. Load		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile
					psi	lbs					
1011863	205/70R15T	96T	6.0	5.0-7.0	44	1,565	26.3	8.2	6.3	13.1	789
1012550	205/75R15T	97T	5.5	5.0-7.0	44	1,609	27.1	8.1	6.3	13.4	766
1011845	235/75R15T	105T	6.5	6.0-8.0	44	2,039	28.8	9.3	7.2	13.4	721
1010142	225/65R16	100T	6.5	6.0-8.0	44	1,764	27.5	9.0	7.1	13.5	756
1010143	235/65R16	103T	7.0	6.5-8.5	44	1,929	28.0	9.4	7.4	13.5	741
1010480	215/70R16	100T	6.5	5.5-7.0	44	1,764	27.9	8.7	6.6	13.5	745
1010138	225/70R16	103T	6.5	6.0-7.5	44	1,929	28.4	9.0	6.9	13.5	731
1010482	235/70R16 XL	109T	7.0	6.0-8.0	50	2,271	28.9	9.5	7.2	13.5	719
1010139	245/70R16	107T	7.0	6.5-8.0	44	2,150	29.5	9.8	7.5	13.5	704
1010483	255/70R16	111T	7.5	6.5-8.5	44	2,403	30.0	10.2	7.8	13.5	692
1010484	265/70R16	112T	8.0	7.0-9.0	44	2,469	30.6	10.6	8.1	13.5	679
1010347	225/75R16	104T	6.0	6.0-7.5	44	1,984	29.3	8.8	6.9	13.5	709
1010348	235/75R16	108T	6.5	6.0-8.0	44	2,205	29.8	9.3	7.2	13.5	696
1010486	245/75R16	111T	7.0	6.5-8.0	44	2,403	30.4	9.6	7.5	13.5	683
1010488	265/75R16	116T	7.5	7.0-9.0	44	2,756	31.7	10.4	8.2	13.5	655
1010134	225/65R17	102T	6.5	6.0-8.0	44	1,874	28.5	9.0	7.1	13.5	729
1010476	235/65R17	104T	7.0	6.5-8.5	44	1,984	29.1	9.4	7.6	13.5	715
1010135	245/65R17	107T	7.0	7.0-8.5	44	2,150	29.5	9.8	7.8	13.5	704
1010129	255/65R17	110T	7.5	7.0-9.0	44	2,337	30.1	10.2	7.9	13.5	691
1010136	265/65R17	112T	8.0	7.5-9.5	44	2,469	30.6	10.7	8.3	13.5	680
1010137	275/65R17	115T	8.0	7.5-9.5	44	2,679	31.1	11.0	8.7	13.5	668
1010477	245/70R17	110T	7.0	6.5-8.0	44	2,337	30.6	9.8	7.5	13.5	680
1010479	265/70R17	115T	8.0	7.0-9.0	44	2,679	31.7	10.7	8.1	13.5	656
1010144	225/55R18	98T	7.0	6.0-8.0	44	1,653	27.8	9.2	7.4	13.5	748
1010145	235/55R18	100T	7.5	6.5-8.5	44	1,764	28.1	9.6	7.7	13.5	738
1010226	255/55R18 XL	109T	8.0	7.0-9.0	50	2,271	29.0	10.4	8.3	13.5	716
1009529	235/60R18 XL	107T	7.0	6.5-8.5	50	2,149	29.1	9.4	7.3	14.0	714
1010227	P245/60R18	104T	7.0	7.0-8.5	44	1,984	29.6	9.8	7.9	13.5	703
1009530	265/60R18T	110T	8.0	7.5-9.5	44	2,337	30.5	10.7	8.2	14.0	681
1009531	P235/65R18	104T	7.0	6.5-8.5	44	1,984	30.0	9.5	7.3	14.0	692
1009533	P255/65R18	109T	7.5	7.0-9.0	44	2,271	31.1	10.2	7.9	14.0	668
1009534	P265/65R18	112T	8.0	7.5-9.5	44	2,469	31.5	10.7	8.2	14.0	659
1009535	P275/65R18	114T	8.0	7.5-9.5	44	2,601	32.1	11.0	8.6	14.0	647
1009536	P255/70R18	112T	7.5	6.5-8.5	44	2,469	32.1	10.2	7.9	14.0	647
1009537	P265/70R18	114T	8.0	7.0-9.0	44	2,601	32.6	10.7	8.2	14.0	637
1010133	255/50R19	103T	8.0	7.0-9.0	44	1,929	29.1	10.4	8.3	13.5	714
1010489	255/60R19	109T	7.5	7.0-9.0	44	2,271	31.1	10.2	7.9	14.0	668
1009538	P265/50R20	107T	8.5	7.5-9.5	44	2,149	30.5	10.9	8.2	14.0	681
1009539	P275/55R20	111T	8.5	7.5-9.5	44	2,403	32.0	11.2	8.6	14.0	649
1009540	P275/60R20	114T	8.0	7.5-9.5	44	2,601	33.0	11.0	8.6	14.0	629
2001686	LT235/75R15	104/101Q	6.5	6.0-7.0	50	1,985	28.9	9.3	7.2	16.5	720
2001423	LT225/75R16	115/112Q	6.0	6.0-7.0	80	2,680	29.3	8.8	7.0	16.5	709
2001420	LT245/75R16	120/116Q	7.0	6.5-8.0	80	3,042	30.5	9.8	7.5	16.5	682
2001442	LT265/75R16	123/120Q	7.5	7.0-8.0	80	3,415	31.7	10.5	8.3	16.5	656
2001421	LT215/85R16	115/112Q	6.0	5.5-7.0	80	2,680	30.4	8.5	6.5	16.5	683
2001422	LT235/85R16	120/116Q	6.5	6.0-7.5	80	3,042	31.7	9.3	7.2	16.5	655
2001434	LT245/70R17	119/116Q	7.0	6.5-8.0	80	3,000	30.6	9.8	7.6	16.5	680
2001426	LT265/70R17	121/118Q	8.0	7.0-8.5	80	3,195	31.7	10.7	8.3	16.5	656
2001689	LT245/75R17	121/118Q	7.0	6.5-7.5	80	3,195	31.5	9.8	7.6	16.5	660
2001425	LT235/80R17	120/117Q	6.5	6.0-7.5	80	3,085	31.8	9.3	7.1	16.5	653
2001690	LT275/65R20	126/123Q	8.0	7.5-9.5	80	3,750	34.1	11.0	8.3	16.5	609
2001708	31X10.50R15LT	109Q	8.5	7.0-9.0	50	2,270	30.5	10.6	8.1	16.5	681

Available Sidewall = BSW
 Recommend for Stud Pin (TSMI No.12 for (P) Metric Sizes and TSMI No.15 for LT Metric Sizes)
 Technical data subject to change without prior notice.