



# ventus V2 concept



- H & V-Rated
- U.T.Q.G. 500/AA/A
- 40/45/50/55 Series

Designed for those with a passion for performance. Ventus V2 Concept's directional tread pattern and compound provide excellent handling, all-season traction and extended tread life. The innovative 'Twister System' 3D Wave Pattern Channel forcibly removes water from the tread contact patch for improved driving in wet conditions and greater control.

## Dimension Data

Pattern Code **H437** **PCR**

S-Code	Size	L / I & SS	Measuring Rim	Rim Width Range	Max. Load		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/Mile
					psi	lbs					
1010609	195/50R15	82H	6.0	5.5-7.0	51	1,047	22.8	7.8	6.2	10.0	911
1010610	205/50R15	86H	6.5	5.5-7.5	51	1,168	23.1	8.3	6.5	10.0	899
1010611	195/55R15	85V	6.0	5.5-7.0	51	1,135	23.5	7.9	6.2	10.0	884
1010613	205/45R16	83H	7.0	6.5-7.5	51	1,074	23.2	8.1	6.8	10.0	895
1010615	205/50R16	87H	6.5	5.5-7.5	51	1,202	24.1	8.3	6.5	10.0	862
1010616	225/50R16	92V	7.0	6.0-8.0	51	1,389	24.9	9.0	7.0	10.0	834
1010617	245/50R16	97H	7.5	7.0-8.5	51	1,609	25.7	9.8	7.7	10.0	808
1011816	185/55R16	83H	6.0	5.0-6.5	51	1,074	24.0	7.6	5.8	10.0	865
1010618	205/55R16	91H	6.5	5.5-7.5	51	1,356	25.0	8.3	6.5	10.0	831
1010650	215/55R16	93H	7.0	6.0-7.5	51	1,433	25.3	8.9	6.7	10.0	821
1010619	225/55R16	95H	7.0	6.0-8.0	51	1,521	25.7	9.1	7.0	10.0	808
1010620	205/40R17 XL	84H	7.5	7.0-8.0	50	1,102	23.5	8.3	6.8	10.0	884
1013815	205/45R17 XL	88V	7.0	6.5-7.5	50	1,235	24.3	8.1	6.8	10.0	857
1012808	215/45R17 XL	91V	7.0	7.0-8.0	50	1,356	24.5	8.4	7.1	10.5	848
1012809	225/45R17 XL	94V	7.5	7.0-8.5	50	1,356	24.8	8.9	7.5	10.0	838
1013816	235/45R17 XL	97V	8.0	7.5-9.0	50	1,609	25.2	9.3	7.8	10.0	824
1013818	245/45R17	95V	8.0	7.5-9.0	51	1,521	25.7	9.6	8.1	10.0	808
1010646	205/50R17 XL	93V	6.5	5.5-7.5	50	1,433	25.1	8.4	6.5	10.0	827
1010647	215/50R17	91V	7.0	6.0-7.5	51	1,356	25.4	8.9	6.7	10.0	818
1010648	225/50R17	94V	7.0	6.0-8.0	51	1,477	25.9	9.1	7.0	10.0	802
1010628	225/40R18 XL	92H	8.0	7.5-9.0	50	1,389	25.1	9.1	7.5	10.0	828
1010631	215/45R18 XL	93H	7.0	7.0-8.0	50	1,433	25.6	8.4	7.1	10.0	811

Available Sidewall = BSW  
 Technical data subject to change without prior notice.